


## **PET Acrylic Adhesive Coating/Masking Tape**

## **Product No.:MAT05**

## MAT053565S/MAT055080S/MAT052565S/MAT052590S

Q-MANTIC® PET acrylic adhesive coating/masking tape is made of polyester film as its base material, which is coated with the acrylic adhesive. The adhesive tape shows excellent adhesion, flexibility and outstanding resistance to high temperature. It is easily peeled off and has no adhesive remain.



- \*Tape with 0.05mm/0.075mm PET release liner can be offered.
- \*Double sides adhesive tape can be offered.



### Characteristic


Characteristic				
Property Name	General Table of Properties			
Color	Green	Green	Green	Red/Green
Basic Thickness (μm)	35	50	25	25
Adhesive Thickness (μm)	25	30	40	65
Total Thickness (μm)	60	80	65	90
Width (mm)	2-98			
Length (m)	33/66			
Adhesive Strength (N/25mm)	6	6	6	8
Elongation (%)	40	50	35	35
Tensile Strength (N/25mm)	135	220	115	135
Break-down Voltage (at 200°C)(KV)	4.2			
Max Temperature (°C/30min)	130			
Storage	20°C 65% R.H			

# **Application**

• It is suitable for electroplating, high temperature baking varnish and powder coating.

# **Packing and Storage**

- Min. slitting width: 3mm
- Core ID: 1" /1.5" / 3"
- Storage: Keep in room temperature. Remove package before use. Recommended for use within 6 months



Chengdu Q-Mantic Industrial Products Co., Ltd.

Tel: +86 28 64660018

E-mail: sales@cdq-mantic.com Website: www.cdq-mantic.com