Chengdu Q-Mantic Industrial Products Co., Ltd. **Technical Information**



Aluminum Foil Adhesive Tape

Product No.:MAT11

Q-MANTIC® Aluminum Foil Adhesive Tape possesses excellent conductivity, plasticity, ductility. It can be applied for precise electronics, cell phone, wire, cable, transform, etc. Resist electromagnetic interference.



Characteristic

Product Name	Base Material Thickness(mm)	Adhesive Thickness(mm)	Total Thickness(mm)	Min.(Max) Width(mm)
Aluminum Foil Adhesive Tape	0. 025	0.035	0.060	3-450
Aluminum Foil Adhesive Tape	0.050	0.035	0.085	3-450
Conductive Aluminum Foil Adhesive Tape	0.030	0.035	0.065	3-450
Conductive Aluminum Foil Adhesive Tape	0.035	0.035	0.070	3-450
Double Conductive Aluminum Foil Adhesive Tape	0.025	0.07	0.085	3-450
Double Conductive Aluminum Foil Adhesive Tape	0.050	0.07	0.095	3-450
PET Conductive Foil Adhesive Tape	0.038	0.035	0.073	3-450
PET Conductive Foil Adhesive Tape	0.050	0.035	0.085	3-450
Storage Condition	25℃ 65% R.H			

Application

■ EMI of transformer, cell phone, PC, PDA, PDP, LED screen.

Packing and Storage

- Min. slitting width: 3mm
- Core ID: 1" /1.5" / 3"
- Storage: Keep in room temperature. Remove package before use. Recommended for use within 6 months



Chengdu Q-Mantic Industrial Products Co., Ltd.

Tel: +86 28 64660018

E-mail: sales@cdq-mantic.com Website: www.cdq-mantic.com