

Copper Foil Adhesive Tape**Product No.:MAT12**

Q-MANTIC® Copper Foil Adhesive Tape possesses excellent conductivity, plasticity, ductility. It can be applied for precise electronics, computer, cell phone, wire, cable, transformer etc. Resist electromagnetic Interference.

**Characteristic**


Product Name	Base Material Thickness(mm)	Adhesive Thickness(mm)	Total Thickness(mm)	Min.(Max) Width(mm)
Copper Foil Adhesive Tape	0.018	0.035	0.053	3-450
Copper Foil Adhesive Tape	0.025	0.035	0.060	3-450
Copper Foil Adhesive Tape	0.035	0.035	0.070	3-450
Copper Foil Adhesive Tape	0.050	0.040	0.090	3-450
Conductive Copper Foil Adhesive Tape	0.018	0.035	0.053	3-450
Conductive Copper Foil Adhesive Tape	0.025	0.035	0.053	3-450
Conductive Copper Foil Adhesive Tape	0.035	0.034	0.070	3-450
Conductive Copper Foil Adhesive Tape	0.050	0.040	0.090	3-450
Double Conductive Copper Foil Adhesive Tape	0.025	0.070	0.095	3-450
Double Conductive Copper Foil Adhesive Tape	0.050	0.070	0.120	3-450
PET Copper Foil Adhesive Tape	0.038	0.035	0.073	3-450
PET Copper Foil Adhesive Tape	0.050	0.035	0.085	3-450
PET Copper Foil Adhesive Tape	0.038	0.035	0.073	3-450
PET Copper Foil Adhesive Tape	0.050	0.035	0.085	3-450
Storage Condition	25°C 65% R.H			

Application

- EMI of transformer, cell phone, PC, PDA, PDP, LED screen.

Packing and Storage

- Min. slitting width: 3mm
- Core ID: 1" /1.5" / 3"
- Storage: Keep in room temperature. Remove package before use. Recommended for use within 6 months

**Chengdu Q-Mantic Industrial Products Co., Ltd.**

Tel: +86 28 64660018

E-mail: sales@cdq-mantic.com

Website: www.cdq-mantic.com